



STANDARDS

PORCHER PARACHUTE FABRIC RANGE

Weight		gr/m ²	NFG 07/150
Breaking strenght	warp	N/5cm	NFG 13934-1
	filling		
Elongation	warp	%	ISO 13937-2
	filling		
Tearing strenght	warp	N	NFG 07/145
	filling		
Stitch tearing strenght	warp weft	N	ISO 9237
Air permeability	Original at 125 Pa	l/m ² /s	

Width	Finish	cm
-------	--------	----

7171	9106	9024	9081	9082	9237	9305
------	------	------	------	------	------	------

45	102	40 - 44	36 - 42	36 - 40	38 - 42	132-146	210-233
420	1300 1250	450 380	440	450 380	490 450	1950 1930	3000 2100
20	20	20 30	20	20 30	20 30	20	
				22	23 23		130 150
55		50	50				290 330
630-830	700-1000	<15	410-610	<120	<15	750-950	

(930) / 1900	1620	1400	920 / 1520	1600	1400/1680	1380	1570/1630
---------------------	-------------	-------------	-------------------	-------------	------------------	-------------	------------------

NEW PRODUCTS

Weight		gr/m ²	NFG 07/150
Thickness		µm	BSEN 5084
Breaking strenght	warp	N/5cm	NFG 13934-1
	filling		
Elongation	warp	%	ISO 13937-2
	filling		
Tearing strenght	warp	N	NFG 07/145
	filling		
Stitch tearing strenght	warp weft	N	ISO 9237
Air permeability	Original at 125 Pa	l/m ² /s	
	Original at 1000 Pa		

Width	Finish	cm
-------	--------	----

PN1	PIA-C 44378 TYPE IV	PN4 Zero Porosity		PN9	PN10 Zero Porosity		
-----	------------------------	----------------------	--	-----	-----------------------	--	--

42	41	44 - 48		30 +/- 3	36,3		
76	76	75		0,06			
400	400	400		350 320	381 312		
22	20	18		22	20 30,7		
22	22	58		18	40,9 41,7		
No spec	No spec	No spec		No spec	No Spec		
15	0,25 - 15			15			
		0,05			0,05		

1230/1600	1230/1600	1230/1600	1230/1600	1600	1680		
------------------	------------------	------------------	------------------	-------------	-------------	--	--

Dold : spec max